

**Allahabad UP Gramin Bank**  
**Regional Office**  
**Near Tourist Bunglow , Chhatarpur Road, Mahoba**

**Ref: -Tender for Supply of 61 Inch Cash Safe BB Class .**

Bank invites sealed tenders from the manufacturers of cash safe/ authorized dealers for supply of 61 inches BB Class cash safe for our branches at different centres in Bank's area of operation in Hamirpur district.

In this context following points are to be noted:

- i) The unit rate as quoted by the manufacturers should be inclusive of cost, all type of charges, transportation charge/delivery charge/taxes etc
- ii) Rates should uniformly be applicable for supply of the cash safe at the branches.
- iii) The rate will remain fixed for at least 6 months from the date of letter of indent.
- (iv) The product should be a CBRI (Central Building Research Institute) certified one.

Duly sealed tenders for all type of cash safes are to be submitted at Bank's Regional office latest by 28.3.2013 upto 2.00 p.m. on the captioned address. Tender will be opened in presence of purchase committee on 30..03.2013 at 4.00 p.m.

- v) The address of bank is given below:-

**Allahabad up Gramin Bank**  
**Regional Office**  
**Near Tourist Bunglow , Chhatarpur Road, Mahoba**

DATE 12.03.2013

**REGIONAL  
MANAGER**

### **Qualifying Criteria for tenderers**

1	The tenderer should fulfill the following qualifying criteria. They shall submit copies of documents to prove their qualifications along with the technical and commercial bids failing which their tenders are liable to be rejected.
2	Only manufacturers of 61 inch BB class cash safes are eligible to submit tenders.
3	The tenderer should have a registered office and distribution set up in Lucknow, Kanpur and should have been dealing with manufacture and supply of cash safes for the last ten years to the Banks.
4	The tenderer should have a well-established and efficient service network at all major cities or near the place where the safes are to be supplied.
5	The tenderer should have supplied in a span of last 5 years, at least 200 numbers of a single order of BB Class cash safes to various Government institutions and PSU banks across the country.
6	The tenderer should furnish audited financial statements for the last 3 years giving segment wise turnover details.
7	The tenderer shall furnish copies of IT assessments orders for the last 3 years.
8	The tenderer shall furnish ST / VAT registration numbers.
9	The tenderer should be an original equipment manufacturer of locks. The lock making process should be computerized and must be based on latest technology.
10	The tenderer should be a total security solutions provider, with capability of offering Banking security products such as cash safe, lockers etc.
11	The Bank reserves the right to make any changes in the terms and conditions of contract. The Bank will not be obliged to meet and have discussions with any vendor and/or to listen to any representations.

### **Technical specifications of cash safe**

1	The safe dimensions and specifications shall be as per IS 550 (Part 1): 2003.
2	The cash safe shall be marked with IS 550 listing mark as per BIS rules.
3	The manufacturers at any given point should be in a position to produce the latest BIS certificate for the cash safe offered and quoted.
4	The safe must have been type – tested at BIS accredited test house for acquiring BIS listing mark and not at any other test house or at manufacturer's premises. Bank has full liberty to ask the supplier of cash safe to send cash safe from the agency nominated by the Bank.
5	On demand manufacturer shall submit ARAI testing report or a letter from BIS office to authenticate ARAI testing.
6	All the surfaces of the cash safe before painting shall be thoroughly degreased and cleaned of rust and scale preferably by sand blasting or by normal pickling process and treated chemically to prevent from rusting.
7	The safe shall be painted inside and outside with an anti – corrosive primer followed by two undercoats of paints and finally painted with quick drying paint.
8	The outer and inner body of cash safe should be made of mild steel conforming to IS 2062 and the total thickness shall be minimum 7 mm thick out of which the outer body plate should be of max 2.5 mm thick and more steel shall be on inner layer.
9	The thickness of door over the bolt work should be minimum 92 mm.
10	Lock should be secured with oxy- acetylene torch protection plate and with automatic relocking device.
11	The thickness of the torch and tool resistant material in the body of the safe as well as in the door shall be minimum 72mm.
12	The cash safe should be such that the bolt work (bolts) should be movable on both sides, no passive inactive bolts will be used.

**TENDER FORM**

<b>S.O.</b>	<b>ITEM</b>	<b>UNIT COST</b>	<b>CST</b>	<b>REBATE</b>	<b>VAT</b>	<b>QUOTED RATE</b>
1	61 Inch, BB Class, TRTL 15 X 6) BIS – 550 (Part – I) 2003, <b>ARAI</b> certified with BIS label.					
2	61 Inch, BB Class, TRTL 15 X 6 BIS – 550 (Part – I) 2003, with BIS certified.					
3	61 Inch, BB Class, TRTL 15 X 6 BIS – 550 (Part – I) 2003, with BIS label.					

The rates quoted are FOR at our Branches located in Bank “s area of operations.

Authorized signatory

Encl:- Detailed literature of items